

dassoXTR Grey Maintenance

The dassoXTR grey is processed by the dyeing reaction between the gray alkaline and the bamboo fibers on the surface of the decking. The color is fixed on the bamboo fibers by reaction. In daily uses, the grey color on the surface will be some changes. Meanwhile, like other natural materials, after bamboo decking is exposed to UV and aging outdoors, the bamboo fiber gradually grays out and the surface color of the bamboo material echoes each other, which makes the appearances more natural. It is normal for decking board to have slight cracks and splinters.

After the product is used for 1 year or longer, the color of the product will change slightly and gradually become gray. It is not recommended to maintain it within the tolerable range



High pressure water gun






Silicon brush





Steel Brush



Decking cleaner

Procedure	Steps	Using Tools
Clean up	In sunny conditions, clean the debris on the decking surface	
Washing	Use regular water gun for cleaning	
Drying	Natural drying for 6-12 hours	

Oiling	Use faxe grey sealer for oiling, the coating amount is 20-30g/m ² If you need a more grey colour, you can choose woca grey oil or other grey oil.	
Drying	Natural drying for 24 hours	

Cautions:

1. Ensuring that there is no rain within 24 hours after the completion of the maintenance.
2. Under the weather with high temperature and high humidity, the actual drying time will be prolonged.
3. It is not recommended to do maintenance at night with low temperature and high humidity.