



## WAX OILED SHOULD APPLIED AS A LAST APPLICATION BEFORE USING YOUR NEW FLOOR

For final protection an extra coat of Hard Wax Oil clear such as Osmo 3032-Satin or Osmo 3065 semi matt or Saicos Wax is needed\*.

## CLEANING AND MAINTENANCE

We do recommend Osmo Wax cleaner, instructions as per below. Wax Cleaner is designed to renovate our hard wax floors that has

been finished with Hard Wax Oil. The Wax Cleaner will clean stubborn stains and leave the surface refreshed with natural hard waxes.

## PREPARATION

Surface should be clean and dry. Use Hoover or vacuum, Dust or damp mop before applying Liquid Wax Cleaner. Heavy use and commercial areas should be regularly cleaned with Osmo WashandCareandwaterpriortoapplyingLiquid Wax Cleaner.

## APPLICATION

Manually- Apply approximately 1 cup per m<sup>2</sup> of Liquid Wax Cleaner with a lint free cloth or nylon pad such as Mirka Mirlo pads for more aggressive cleaning.

Using Liquid Wax Cleaner regularly will ensure the surface will be more resistant to dirt and wear and tear.

**COVERAGE:** 40-50m<sup>2</sup> for 500ml

**DRYING:** 30-40 minutes

### FOR WHITE FLOOR:

Bianco, Pure – Wax cleaner (3087)

### FOR OTHER:

Wax cleaner (3029)

**\* Always try on small parts or off cut prior to applying whole area.**

**Saicos Wax should not apply on Snow White/Bianco and Pure**

## LONG-TERM MAINTENANCE PROPERLY MAINTAINED:

Vacuum regularly. Remove sticky spills and clean regularly with a cloth or mop dampened with OSMO Wash & Care diluted in water. Don't slosh water onto the floor. Just as with any floor finish, high-traffic areas will show wear overtime. Prompt attention restores the finish. Clean thoroughly. Dry. Then moisten fine steel wool or a white Scotchbrite pad with OSMO Liquid Wax Cleaner. Rub onto the surface.

### Disclaimer on Extra Coat/Applications:

\*\*Our application advice is provided to the best of our knowledge and based on experiments, however, applies only as a non-binding recommendation and does not exempt you from testing the products supplied by us as to their suitability for the intended purpose. Since the application and processing of the products is beyond our control, the responsibility rests solely with the user. With publishing a new technical data sheet the previous loses its validity.

\* Always try on small parts or off cut prior to applying whole area  
Saicos Wax should not apply on Snow White/Bianco and Pure