

# Maintenance Engineered Flooring



Maintenance of your hardwood floor is very easy, the key is upkeep, namely cleaning your floor often and thoroughly - but not too thoroughly.

Please note that you **SHOULD NOT** use any chemicals and abrasives as they can scuff, scratch or even remove your floor's finish and gloss, the floor should be cleaning with a wet mop. We recommend to use felt protectors under the legs or bottoms of heavy furniture, chairs, etc. and to avoid wearing spike-heeled shoes or damaged shoes on the floor as they can cause damage.

## Regular cleaning

When your floor is UV oiled or UV lacquered, we recommend applying maintenance UV oil/ UV lacquered. That can be done few months after the floor was laid.

Placing mats at all points in the home with exterior entrances to avoid debris being tracked onto the flooring will help keep it clean and in a good state.

A good procedure to clean your floors in an efficient and proper manner is to initially sweep the area with a soft bristle broom or Hoover it. It is important to examine the broom's bristles before starting, as some brooms are not appropriate for some surface areas and can also scratch or mar the finish. It is best to try the broom on a small area of the floor first to insure that it's not damaging the floor in any way.

This should be sufficient in most cases and if this procedure is maintained on a regular basis, you will certainly prolong the beauty of your floors for a very long time.

In cases where you have rough stains, you can clean your floor with a damp cloth/ mop, please make sure it will not be soaked as wood and water do not mix well together. Evenly mop the entire surface area until clean, and then let the area air dry.

If you have any spillages, we highly recommend to clean the area as fast as possible to prevent long term staining to the floor

Beyond this, there are other steps that can be taken less frequently that can add life and beauty to your floors, such as floor treatments.

## Regular Floor Treatment

For UV oiled and UV lacquered finishes, Re-oiling you floor every few months can help protect and preserve the flooring beautiful look. Be sure to verify the contents and application procedures for your specific product.

Doing this every few months or so is perfectly safe for your floor's finish and will add that desired effect of longevity and beauty to your home.

## Disclaimer on Extra Coat/Applications:

\*\* Our application advice for maintenance oil/wax is provided to the best of our knowledge and based on experiments, however, applies only as a non-binding recommendation and does not exempt you from testing the products supplied by us as to their suitability for the intended purpose. Since the application and processing of the products is beyond our control, the responsibility rests solely with the user. With publishing a new technical data sheet the previous loses its validity.

## IMPORTANT NOTE





Site conditions are extremely important and make all the difference to a timber floor. Site check before starting installation ensure moisture conditions required met is vital. Wood flooring will perform best when the domestic relative humidity range between 40%-65% and a temperature range of 18-24°C. Wood is a moisture absorbent material and its moisture level varies with air humidity and temperature.

### FOR EXAMPLE

- A.** 50% air humidity and 20°C temperature average Oak floor will have 9% moisture content.
- B.** 30% humidity and 25°C temperature the same Oak floor will have 5% moisture content. As air humidity changes so does the dimension of the wood.

*The overall fabric (walls & floors) of a building should be thoroughly dry (so there are no visible signs of moisture or condensation when heating is on) before bringing in any timber.*

## WOOD&BEYOND LTD

-  877 Finchley Road, NW11 8RR London, UK
-  0203 869 0900
-  [info@woodandbeyond.com](mailto:info@woodandbeyond.com)
-  [www.woodandbeyond.com](http://www.woodandbeyond.com)